

Harrington Signal Inc.
2519 4th Avenue, Moline, Illinois 61265
P.O. Box 590, Moline, Illinois 61266-0590
Phone: (800) 577-5758 Local: (309) 762-0731 Fax: (309) 762-8215
Internet: www.harringtonfire.com



Description

The Harrington HSPS Series Explosion Proof and Weatherproof Non-Coded Manual Pull Stations provide the most reliable manually activated input signal for early warning signaling on supervised or non-supervised alarm systems.

The HSPS Series station is UL listed for use in hazardous locations classified Class I, Groups B, C & D; Class II, Groups E, F & G; and Class III locations, Div. 1. It is also UL listed for use in weatherproof applications classified NEMA 4X.

The "T" pull lever, mounted on the die cast housing, is constructed of die cast aluminum, and is painted white with raised lettering painted red that reads "PULL DOWN". When the "T" lever is activated (pulled), it allows the plunger on the contact arrangement to be activated.

The HSPS Series stations come standard with an allen wrench for locking, resetting and testing. With the "KL" option, a key is used to lock, reset or test the station.

When the "T" pull lever has been pulled, it remains protruding out from the HSPS Series station at a 90 degree angle until the die cast housing is opened by either the allen wrench or key (depending on the model being used).

When the die cast housing is opened, the "T" pull lever may be reset to the normal operating position.

The HSPS Series stations can be tested without the need to pull the "T" pull lever by using the allen wrench or key (depending on the model being used) to open the die cast housing. Opening the die cast housing allows the plunger on the contact arrangement to be activated, thus sending a signal to the control panel.

The HSPS Series station can be used with or without a break glass rod positioned in front of the "T" Pull lever. The glass rod is not needed to hold the "T" pull lever in its normal operating position.



The HSPS Series stations have an optional Dual Action feature. The Dual Action option is a metal cover that lies over the "T" pull lever. The Dual Action cover is painted red with the words "LIFT & PULL" silk screened in white.

To activate the HSPS Series Dual Action station, the Dual Action cover needs to be lifted and then the "T" pull lever can be pulled. The Dual Action cover has a brass knob located at the bottom center, which is used to lift it up.

Ordering Information

Model Number	Part Number	Description
HSPS-6T-LP-EXP-WP	238-0116	Dual action, explosion & weatherproof, terminal connections, (2) NO/COM/NC (form C) contacts
HSPS-6T-KL-EXP-WP	238-0167	Single action, explosion & weatherproof, terminal connections, key lock/reset, (2) NO/COM/NC (form C) contacts
HSPS-6T-KL-LP-EXP-WP	238-0135	Dual action, explosion & weatherproof, terminal connections, key lock/reset, dual action, (2) NO/COM/NC (form C) contacts
HSPS-6T-EXP-WP	238-0170	Single action, explosion & weatherproof, terminal connections, single action, (2) NO/COM/NC (form C) contacts
HSPS-6T-DAH-EXP-WP	238-0178	Dual action, explosion & weatherproof, terminal connections, break glass adapter, (2) NO/COM/NC (form C) contacts

Features

- UL Listed and CSFM Listed
- Explosion Proof and Weatherproof Housing
- Durable Die Cast Housing
- 3/4" Conduit Openings
- Corrosion Inhibit Surfaces
- Terminal Block Connection
- D.P.D.T. Contact Switch
- 10 Amp Snap Action Switch
- Single or Double Action
- "T" Pull Handle Operated
- Allen Wrench or Key Lock/Reset

Applications

The HSPS Series pull stations have a wide variety of features, which makes it ideal for grainaries, flour mills, oil refineries, mines, tankers and many other applications indoor and/or outdoor.

HSPS Series Explosion Proof and Weatherproof Specifications

Electrical

DPDT Switch Contacts	10 Amp @ 120 VAC
Key Switch5 Amp @ 30 VDC

Dimensions

Width	3.2 inches
Length	4.75 inches
Depth	5 inches
Weight	3 lbs.

NOTICE: The information contained in this document is intended only as a summary and is subject to change without notice. The devices described in this document have specific instruction sheets which cover various technical, limitation and liability information. Copies of these instruction sheets and the General Product Warning and Limitations Document, which also contains important information are provided with the product and are available from Harrington Signal Inc. Fire Alarm. Information contained in these documents should be consulted before specifying or using the product. For further information or assistance concerning particular problems contact Harrington Signal Inc. Harrington Signal Inc. Fire Alarm reserves the right to change specifications without notice.